

SONO/MAX25[®]

SOUNDPROOF SUBFLOOR

Short installation sheet Sono/Max25

IMPORTANT: Before opening the package, let the SONO/MAX25 sit for 24 hours in the room where it will be installed. Make sure the room temperature does not go below 18 C (64 F) with 40 to 55% humidity. In order for the installation to be optimal, make sure that the subfloor (concrete slab) is completely flat. There should be no undulation or irregularities on the floor surface. Using a ruler or a level, check to see if the subfloor (concrete) is 3/16" thick over a length of 10' or 1/8" thick over a length of 6". If there are irregularities to be filled, be sure to use a cement-based filling compound with a capacity of 3000 lb/in. Install a 6 mm polyethylene on the floor to be covered if recommended by the manufacturer.

To get superior soundproofing performances provided by our SONO/MAX25 products, install the product under 3/4 inch engineering wood (nailed) fig; 1-2

Always leave at least 1/2 inch between the SONO/MAX25 system and the walls, ducts, columns, etc.

First row fig. 1: Cut the panel in half lengthwise (5" × 48"), textured side upward, and insert the profiled slats. The slat must surpass the panel's joints by at least 8". Next rows: Alternate panels in echelon. Fig; 1

Do not install 12" wooden slats or shorter onto SONO/MAX 25. If such an event occurs, a 1/2" plywood board should be installed and screwed prior to installing the wood. Install a vapour barrier (waxed and translucent) between the SONO/MAX 25 and the wood (for new construction with a concrete structure). To secure the wood to the SONO/MAX 25, use only 1½" pins, which should not come into contact with the subfloor, you must respect the recommendations.



You can also install the SONO/MAX25 under ceramic and marble, under floating engineering floor or laminate flooring. It can also replace concrete screed: see all mounting possibilities and references on the website: www.sonomax25.com

Any installation that does not conform to the description sheet voids the SONO/MAX25 warranty.

Please refer to the website. SONO/MAX25 is guaranteed against any manufacturing defect.